

Ozone Generator Cell FQM-G10



BEYOK
百悦康☆☆☆☆

Ozone Output:	8-10g/hr
Generating Method:	Corona Discharge
Electrical:	AC220V-AC110V, 90W
Output Connection:	3/8-inch Plastic joint
Accessory:	Hose +Air stone (Optional)
Cooling fan:	2m3/min
Ozone Control:	Adjustable
Dimension(LxWxH):	8.6"*3.4"*3.5"(218*86*88mm); 6.5"*2.6"*2.2"(164*66*55 mm)
Installation Dim.(LxW):	3.5"*3"(90*76mm); 5.8"(147 mm)
Net Weight:	- kg

The FQM-G series ozone generator cells with ceramic discharge body have good cooling condition, they can provide stable and efficient ozone output, easy to install, operate and maintain.

Features:

- Long working life
- Good cooling condition
- Stable & efficient ozone output
- External dry air or O₂ source
- The core module of mini ozone generator

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Mini air purification and disinfection equipment: medical equipment, incubator, air curtain, air condition, exhaust duct, workshop, hospital
- Mini water treatment equipment: swimming pool, landscape pool, waste yard

Size View:

