

Ozone Generator Cell FQM-G20A



BEYOK
百悦康☆☆☆☆

Ozone Output:	5-10g/hr@30LpmAir;15-20g/hr@5Lpm O2
Ozone Generating Method	Corona Discharge
Electrical:	AC220V-AC110V, MAX 150W
Ozone Output Connection:	3/8-inch Plastic joint
Accessory:	Hose +Air stone (Optional)
Cooling Water:	2m3/min
Ozone Control	50-100% Variable
Dimension(LxWxH):	15.4"*3.7"*2.6"(390*93*65 mm); 6.6"*3.8"*3.5"(168*96*88 mm)
Installation Dimension(LxW):	13.6"*1.2"(346 *30 mm); 5.8"*3.2"(148*82 mm)
Net Weight:	- kg

The FQM-G series of BEYOK ozone generator cells with ceramic discharge body have good cooling condition, they can provide stable and efficient ozone output, easy to install, operate and maintain.

Features:

- Ozone Generation cell for water purification
- 20g/hr ozone output
- Long-time continue working
- Good cooling condition
- Stable & efficient ozone output.
- External dry air or O2 source
- The core module of mini ozone generator

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Mini air purification and disinfection equipment: medical equipment, incubator, air curtain, air condition, exhaust duct, workshop, hospital
- Mini water treatment equipment: swimming pool, landscape pool, waste yard

Size View:

