

Ozone Generator Cell FQM-G50W



BEYOK
OZONE

Ozone Output:	30-50g/hr@10Lpm O ₂
Ozone Generating Method:	Corona Discharge
Electrical:	AC220V-AC110V, MAX600W
Ozone Output Connection:	3/8-inch Plastic joint
Accessory:	Hose +Air stone (Optional)
Cooling Water:	3L/min, 68°F, 0.15MPa
Ozone Control:	50-100% adjustable
Dimension(LxWxH):	28.0"×3.4"×4.3"(710×87×111 mm); 9.8"×5.4"×2.9"(249×138×73 mm)
Installation Dimension(LxW):	26.3"×1.7"(670×43 mm); 8.2"×4.6"(210×115 mm)
Net Weight:	- kg

The FQM-G series of BEYOK ozone generator cells with ceramic or glass discharge body have good cooling condition, they can provide stable and efficient ozone output, easy to install, operate and maintain.

Features:

- Long working life
- Good cooling condition
- Stable & efficient ozone output.
- External dry air or O₂ source
- The core module of mini ozone generator.

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Mini air purification and disinfection equipment: medical equipment, incubator, air curtain, air condition, exhaust duct, workshop, hospital
- Mini water treatment equipment: swimming pool, landscape pool, waste yard

Size View:

