

Ozone Generator Cell FQM-P3500



BEYOK
OZONE

Ozone Output:	3500 mg/hr*
Ozone Generating Method:	Corona Discharge
Electrical:	AC220V-AC110V, 40W
Ozone Output Method:	Release into the air directly
Accessory:	None
Case:	Plastic
Circuit Dimension(LxWxH)	5.7"*2.2"*2.5"(126*56*64 mm)
Ceramic Plate Dimension(LxW):	3.5"*2.0"(90*50 mm)
Installation Dimension:	5.2"(132 mm)
Net Weight:	0.35 kg

The FQM-P series of BEYOK ozone generator cells with ceramic discharge body are mainly used for air disinfections and sterilizations, they can provide stable and efficient ozone output, easy to install, operate and maintain.

Features:

- Widely used in large quantities
- Reliable quality
- Stable & efficient output
- Integrated design two in one unit with ozone ceramic and ozone power
- Using "high-frequency ceramic creeping discharge" generated ozone technology

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection cabinet, wardrobe, dryer, refrigerator, incubator, toilet.
- Medical equipment, air purifier, beauty equipment, car, air conditioning, ventilation, air curtain machine.

Size View:

