

## Ozone Water Generator FQW-M300



**BEYOK**  
百悦康☆☆☆☆☆

Ozone Output:	200-300 mg/hr @ air
Water flow:	3-5 L/min
Ozone water conc.:	1.0-3.0 ppm
Generating method:	Corona Discharge
Mixing method:	Venture ejector
Electrical:	DC12V-AC220V-AC110V, 10 W
Water Connector:	G1/2 Male plastic joint
Case:	Plastic
Dimension(LxWxH):	3.9**3.9**1.8"(100*100*46 mm)
Net Weight:	1.0 lbs (0.5 kg)

The FQW-series of BEYOK ozone water generator use ozone core discharge of invention patent, including the integration design of ozone generator tube, ozone driving circuit, check valve and venture ejector, they can provide stable and efficient ozone water output, easy to install and maintain.

### Features:

- Invention patent technology
- Integrated design in one unit with driving circuit, ozone tube and venture ejector
- Stable & efficient output
- Without pump, low noise
- Fan cooling inside
- Long working life

### Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

### Application:

- Washing machine, dishwasher, water machine, water purification machines, coin-operated sale water, fruit and vegetable detoxification machines
- Aquatic animals, the spa machine, surfing bathtub, Medical equipment, beauty equipment

### Size View:

