

Airpipe Air Purifier **GQA-P20**



Ozone Output:	20 g/hr; 40ppm
Ozone Generating Method:	Sheet Multi-Group Air Gap Discharge
Electrical:	220V/50Hz, 200W
Air volume:	300m3/h
Control:	Programmable controller
Install method:	Floor or back hanging
Application Range:	400-600 m3
Case:	Stainless steel
Dimension(LxWxH):	15.7"*10.8"*25.6" (400*300*650 mm)
Net Weight:	17 kg

The GQA-P series of BEYOK airpipe air purifiers using pipeline connection make ozone mixed into the pipeline airflow, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for the places which have air conduit, such like food factory assembly lines, restaurants, and refrigerated storages, etc.

Features:

- Pipeline
- Simple operation
- High efficiency
- Strong ventilation
- Good dispersion
- Low cost
- Easy to maintain

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- Food fresh keeping: refrigerated storage.
- Deodorization: basement, garage, store room, hotel.

Size View:

