

Airpipe Air Purifier GQA-P60



| | |
|--------------------------|-------------------------------------|
| Ozone Output: | 60 g/hr; 120ppm |
| Ozone Generating Method: | Sheet Multi-Group Air Gap Discharge |
| Electrical: | 220V/50Hz, 450W |
| Air volume: | 300m3/h |
| Control: | Programmable controller |
| Install method: | Floor or back hanging |
| Application Range: | 1200-3000 m3 |
| Case: | Stainless steel |
| Dimension(LxWxH): | 15.7"*10.8"*25.6" (400*300*650 mm) |
| Net Weight: | 19 kg |

The GQA-P series of BEYOK airpipe air purifiers using pipeline connection make ozone mixed into the pipeline airflow, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for the places which have air conduit, such like food factory assembly lines, restaurants, and refrigerated storages, etc.

Features:

- Pipeline
- Simple operation
- High efficiency
- Strong ventilation
- Good dispersion
- Low cost
- Easy to maintain

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- Food fresh keeping: refrigerated storage.
- Deodorization: basement, garage, store room, hotel.

Size View:

