

Mobile Ozone Generator **GQO-C10G**



Ozone Output:	3-5g/hr@15Lpm Air; 8-10g/hr@3Lpm O2
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 150W
Gas Source Input:	Built-in air pump
Control:	Programmable electronic loop controller
Inlet & Outlet Connection:	0.3"*0.2"(8*6mm)Stainless steel& Hose
Application Range:	100-300 m3
Case:	Stainless steel
Dimension(LxWxH):	25.6" *13.8" *9.8" (650*350*250 mm)
Net Weight:	- kg

The GQO-C series of BEYOK mobile ozone generators can mix ozone into water to destroy bacteria, purify air and eliminate peculiar smell. They are suitable for food factory assembly lines, restaurants, and refrigerated storages, etc. Connect to the external oxygen source will provide a higher concentration of ozone.

Features:

- Mobile & Wheeled
- Compact design with built-in air pump
- Simple operation
- High efficiency
- High concentration
- Work continuously
- Economical and low running cost
- Oxygen or dry air feed
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- Food fresh keeping: refrigerated storage.
- Deodorization: basement, garage, store room, hotel.

Size View:

