

Desktop Ozone Generator **GQO-D10W**



Ozone Output:	8-10 g/hr@5Lpm O ₂
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 150W
Ozone Control:	50-100% variable
Control:	Outer loop timer
Cooling Method:	Air cooled
Inlet & Outlet Connection:	0.3"×0.2"(8*6mm)Stainless steel& Hose
Case:	Plastic coated Aluminum
Dimension(LxWxH):	14.3" *14.2" *6.1" (362*360*155 mm)
Net Weight:	19.8 lbs (9.0 kg)

The GQO-D series of BEYOK desktop ozone generators designed separate ozone generating units can be multilayer placed to increase the ozone output. Connect to the external oxygen source will provide a higher production of ozone.

Features:

- Desktop & Portable
- 50~100% variable ozone output control
- Compact design and simple operation
- Oxygen or dry air feed
- High efficiency
- Work continuously
- Economical, and low running costs
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- Food fresh keeping: refrigerated storage.
- Deodorization: basement, garage, store room, hotel.

Size View:

