

Skid-mounted Ozone Generator GQO-P100R



Ozone Output: 100g/hr@20L/min O2 external

Ozone Generating Method: Corona Discharge

Electrical: 220V/50Hz-120V/60Hz, 1200W Gas Source Input: Connect to external gas source

Control: Programmable electronic loop controller Inlet & Outlet Connection: 0.3"*0.2"(8*6mm) Stainless steel& Hose

Cooling Method: Air cooled

Case: Metal

Dimension(LxWxH): 20.5" *13.8" *22.8" (520*350*580 mm)

Net Weight: -lbs (- kg) Adapted swimming pool: 1500m3

The GQO-P-R series of BEYOK skid-mounted ozone generators can product high concentration ozone, adopting the latest flat panel ozone technology. Connect to the external oxygen source will provide a higher concentration of ozone. They are suitable for swimming pool, food factory assembly lines, restaurants, and refrigerated storages, etc.

Features:

- · Flat panel ozone technology
- · Skid-mounted
- · Simple operation
- · High efficiency
- · High concentration
- · Work continuously
- · Economical and low running cost
- · Oxygen or dry air feed

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- · Without ozone residual and secondary pollution

Application:

- · Disinfection: Swimming pool and small water treatment.
- · Food fresh keeping: restaurant, refrigerated storage.
- · Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

Size View:

