

Skid-mounted Ozone Generator **GQO-P200R**



Ozone Output:	200g/hr@40Lpm O2 external
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 1600W
Gas Source Input:	Connect to external gas source
Control:	Programmable electronic loop controller
Inlet & Outlet Connection:	0.3"*0.2"(8*6mm) Stainless steel& Hose
Cooling Method:	Water cooled
Case:	Stainless steel
Dimension(LxWxH):	15.7" *13.8" *39.4" (400*350*1000 mm)
Net Weight:	-lbs (- kg)
Adapted swimming pool:	2500m3

The GQO-P-R series of BEYOK skid-mounted ozone generators can product high concentration ozone, adopting the latest flat panel ozone technology. Connect to the external oxygen source will provide a higher concentration of ozone. They are suitable for swimming pool, food factory assembly lines, restaurants, and refrigerated storages, etc.

Features:

- Flat panel ozone technology
- Skid-mounted
- Simple operation
- High efficiency
- High concentration
- Work continuously
- Economical and low running cost
- Oxygen or dry air feed

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection: Swimming pool and small water treatment.
- Food fresh keeping: restaurant, refrigerated storage.
- Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

Size View:

