

Wall Mounted Ozone Generator **GQO-V07**



BEYOK
百悦康☆☆☆☆

Ozone Output:	10 g/hr@30Lpm Air, with air pump inside
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 100W
Pump Output:	20-30 L/min, 20KPa
Control:	Outside connect to system control board
Cooling Method:	Air cooled
Inlet & Outlet Connection:	0.3"*0.2"(7*4mm) plastic joint& Hose
Case:	Plastic
Dimension(LxWxH):	15.7" *14.8" *7" (400*375*179 mm)
Net Weight:	-lbs (- kg)

The GQO-V series of BEYOK wall mounted ozone generators can mix ozone into water to destroy bacteria, purify air and eliminate peculiar smell. Connect to the external oxygen source will provide a higher concentration of ozone.

Features:

- Wall mounted
- Compact design and simple operation
- Oxygen or dry air feed
- High efficiency
- Work continuously
- Economical, and low running costs
- Long working life


Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: lab, water tank, food factory.
- Deodorization: basement, garage, store room, hotel.
- Industrial application: environmental chamber.....

Size View:



BEYOK.com