

Mobile Ozone Water System **GQW-M16**



Ozone Output:	12-16g/hr@5Lpm	O ₂	Built-in	O ₂
Ozone Generating Method:	Corona Discharge generation system			
Electrical:	220V/50Hz-120V/60Hz, Max.1500W			
Ozone Control	50-100% variable			
Control:	Programmable controller			
Water Processing Volume:	2-4mg/L@1-2TPH			
Water Connection:	1/2" Stainless steel screw			
Case:	Stainless steel			
Dimension(LxWxH):	31.5" *15.7" *27.2" (800*400*690 mm)			
Net Weight:	- kg			

The GQW-M series of BEYOK mobile ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for large places which need to clean with ozone water directly like slaughter houses etc.

Features:

- Mobile
- Compact design
- Simple operation
- 50~100% variable ozone output control
- Gas-water mixing system
- Easy to maintain
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: canteen, hospital, swimming pool, slaughter house, water filling production line.
- Deodorization: hotel, central air-conditioning cooling tower

Size View:

