Desktop Ozone Generator GQO-D10A



BEYOK 百悦康

Ozone Output:	5-10 g/hr@15Lpm Air or 3Lpm O2
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 130W
Pump Output:	10-15 L/min, 20KPa, inside
Ozone Control	50-100% variable
Cooling Method:	Air cooled
Inlet & Outlet Connection:	8*6mm Stainless steel& Hose
Case:	Plastic coated Aluminum
Dimension(LxWxH):	347*145*300 mm
Net Weight:	5.0 kg

The GQO-D series of BEYOK desktop ozone generators designed separate ozone generating units can be multilayer placed to increase the ozone output. Connect to the external oxygen source will provide a higher production of ozone.

Features:

- Desktop
- 50~100% variable ozone output control
- Compact design and simple operation
- Oxygen or dry air feed
- High efficiency
- Work continuously
- Economical, and low running costs
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- Food fresh keeping: refrigerated storage.
- Deodorization: basement, garage, store room, hotel.

Size View:

